

# Full Size ATX Motherboard AS-C74

Support 2nd Generation Intel® Core™ i7/ i5/ i3/  
Pentium/Xeon® Desktop Processor  
Onboard VGA, DVI, HD Audio, Serial ATA,  
Intel® Gigabit LAN



<b>Form Factor</b>	Full Size ATX motherboard
<b>CPU</b>	Supports 2nd Generation Intel® Core™ i7/ i5/ i3/ Pentium/Xeon® Desktop Processor Package type: FCLGA1155
<b>Memory</b>	Four DDR3 1066/1333 DIMM up to 32 GB
<b>Chipset</b>	Intel® BD82Q67 PCH
<b>Real Time Clock</b>	Chipset integrated RTC with onboard lithium battery
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1min/s ~ 255min/s
<b>Power Management</b>	ACPI 1.0 compliant, supports power saving mode
<b>Serial ATA Interface</b>	Intel® Q67 PCH built-in 4 x Serial ATAII interface up to 300MB/s & 2 x Serial ATAIII interface up to 600MB/s Support RAID 0, 1, 5, 10 and Intel Rapid Storage Technology.
<b>VGA Interface</b>	Intel® Clear Video integrated HD Graphics Technology
<b>DVI Interface</b>	Onboard Chrontel CH7318C DVI Transmitter for DVI interface
<b>Audio Interface</b>	Intel® integrated Q67 with Realtek ALC888 HD Audio.
<b>LAN Interface</b>	Two Intel® 82574L Gigabit LAN.
<b>GPIO interface</b>	Onboard programmable 8-bit Digital I/O interface.
<b>Extended Interface</b>	One PCIE X 16 slot, One PCIE X 4, One PCIE Mini card, One Mini PCI socket, Five PCI slot.
<b>Internal I/O Port</b>	1 x RS232/422/485, 1 x GPIO port, 1 x CDIN connector, 1 x Audio connector, 1 x IrDA connector, 1 x SMBUS connector, 2 x Serial Port and 8 x USB ports, 1 x Parallel port.
<b>External I/O Port</b>	1 x PS/2 Keyboard/Mouse Port, 2 x RJ45 LAN ports, 1 x DB15 VGA port, 4 x USB2.0 ports and 3 x Serial Port.
<b>External Audio</b>	Line-in, MIC-in, Front, Rear, Center/Subwoofer and Optical SPDIF outputs.
<b>Power Requirement</b>	Standard 24-pin ATX power supply (20-pin is compatible) Standard 8-pin 12V power Input connector (4-pin is compatible)
<b>Dimension</b>	307mm x 244mm (L x W)
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20~85 centigrade

## Ordering Code

<b>AS-C74</b>	Onboard VGA, DVI, 2 x Gigabit LAN, 10 x USB2.0, 6 x serial Port, 6 x SATA, 1 x IrDA Realtek HD 5.1CH Audio, Mini-PCI, PCI, PCIE Minicard, PCIE x16.
---------------	--

HS Italia  
Tel. 0536 830620  
Fax. 0536 831215  
[www.hs-italia.it](http://www.hs-italia.it)  
[info@hs-italia.it](mailto:info@hs-italia.it)

