

## Mini-ITX motherboard

### LV-67I

Intel® Atom™ Processor with DDRIII SO-DIMM, VGA, DVI, LVDS, Gigabit LAN, USB2.0, HD Audio, Serial ATAII, PCI, Mini PCI, PCIE mini card, LPC, LPT



<b>Form Factor</b>	Mini-ITX Motherboard
<b>CPU</b>	Intel® Atom™ CedarTrail Processor with optional D2700 or N2800 Package type : FCBGA559
<b>Memory</b>	2 x DDRIII SO-DIMM 800/1066 MHz up to 4GB,(SO-DIMM2 Primary) Support Non-ECC, unbuffered memory only
<b>Chipset</b>	Intel® NM10
<b>Real Time Clock</b>	Chipset integrated RTC with onboard lithium battery
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1min/s ~ 255min/s
<b>Power Management</b>	Supports ACPI 3.0 compliant
<b>Serial ATA Interface</b>	2 x serial ATAII interface with 300MB/s transfer rate
<b>Integrated Graphics</b>	Intel® integrated extreme GMA 3650(Graphic Media Accelerator) Technology
<b>VGA Interface</b>	Onboard DSUB15 connector for VGA interface
<b>LVDS Interface</b>	Onboard 18-bit single channel LVDS connector with +3.3V/+5V supply ( N2800 ) Onboard 18 and 24-bit single channel LVDS connector with +3.3V/+5V supply ( D2700 )
<b>DVI interface</b>	Onboard DVI interface with 20-pin connector
<b>Audio Interface</b>	REALTEK ALC888 HD Audio
<b>LAN Interface</b>	2 x Intel® 82583V Gigabit Ethernet controller
<b>GPIO Interface</b>	Onboard programmable 8-bit Digital I/O interface
<b>Extended Interface</b>	1 x PCI slot, 1 x mini PCI, 1 x PCIE mini card
<b>Internal I/O Port</b>	3 x RS232,1 x SMBUS, 1 x GPIO, 2 x USB2.0 ports, 1 x IrDA, 1 x DVI , 1 x LVDS, 2 x Serial ATAII, 1 x LPT, 1x LPC, 1 x HD Audio and 1 x CDIN
<b>External I/O Port</b>	1 x PS/2, 2 x RJ45, 1 x VGA, 4 x USB2.0, 1 x RS232/422/485, 2 x RS232, 1 x SPDIF and 1 x HD Audio
<b>Power Requirement</b>	Standard 20-pin ATX power supply or 9~24V full range DC Input
<b>Dimension</b>	170mm x 170mm
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20~85 centigrade

#### Ordering Code

<b>LV-67ID</b>	Support Intel® Atom™ CedarTrail D2700 processor with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAII, SMBUS, LPC, LPT, GPIO, PCI, Mini PCI, PCIE mini card.
<b>LV-67IN</b>	Support Intel® Atom™ CedarTrail N2800 processor with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAII, SMBUS, LPC, LPT, GPIO, PCI,Mini PCI, PCIE mini card.

HS Italia  
Tel. 0536 830620  
Fax. 0536 831215  
[www.hs-italia.it](http://www.hs-italia.it)  
[info@hs-italia.it](mailto:info@hs-italia.it)

